

PTSC

Intermediate


AXC.11.05

General Information

PTSC stands for para toluene sulfonylchloride also named tosylchloride or abbreviated TsCl. It serves as intermediate in pharmaceuticals and in various chemical synthesis.

Description and Application

PTSC is an intermediate in chemical and pharmaceutical synthesis. Among others it is an activation agent in the synthesis of organic compounds. One major application of PTSC is the tosylation of alcohols in order to activate the group for conversion at a later step in the synthesis. Through the use of PTSC an alcohol can be converted into an excellent leaving group, as depicted in below schema:



NH₃ is taken as example but it can be done with any organic nucleophile.

PTSC is also used to convert carboxylic acids into phenolic esters through the use of the weak nucleophiles like phenols.

Many pharmaceuticals are prepared with PTSC as activating agent as for example:

- Flupentixol (psychiatric drug)
- Thiometon (pesticide)
- Deltamethrine (pesticide)
- Diboc (protecting agent)
- Cefotaxime (antibiotic)
- MDMA (psychiatric drug)

Specifications

Active content:	≥ 99.5%
Water content:	≤ 0.1%
Crystallisation point:	≥ 66.9°C
Colour *):	≤ 40 Pt/Co
p-toluenesulfonic acid:	≤ 0.2%
o-toluenesulfonylchloride:	≤ 0.3%

*) 25 % solution in acetone

Physical Properties

Apparent bulk density:	660 - 730 kg/m ³
Appearance:	white crystalline powder*
Boiling point (1.33 kPa):	135.5°C
Flash point (closed cup):	128°C

*Little coloured spots can be found on the surface of the powder due to moisture condensation.

Toxicological information

Acute toxicity (oral):	LD50 rat > 4680 mg/kg
Genotoxicity (Amestest):	not mutagenic
Biotic degradation:	readily biodegradable

Packaging

- 25 kg polyethylene drums, 24 on a pallet.
- 100 kg polyethylene drums, 4 on a pallet.

Storage

Store in a cool dry place.

Think about your impact on the environment: reduce, reuse or recycle! Contact Axcentive if you feel we could be of help.

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control, we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestions.

KETJENFLEX® is a registered trademark of Axcentive SARL

Europe, Americas, Middle East and Africa
Axcentive SARL
Chemin de Champouse
13320 Bouc Bel Air, France
Phone: +33 4 42 69 40 90
E-mail: info@axcentive.com
Web: www.axcentive.com

Asia, India and Australasia
Axcentive Asia Pte Ltd
13 Lorong 8 Toa Payoh, #07-01 Braddell Tech Park
319261 Singapore
Phone: +65 6258 6338
E-mail: info@axcentive.com
Web: www.axcentive.com