



SAFETY DATA SHEET

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

ETHYLENEDIAMINE 90% (EDA90%)

Version: 13
Version Date: 25/07/2023

Page: 1/57

1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY UNDERTAKING

1.1 Product identifier

Trade name	Allamine EDA90
Substance name	Ethylenediamine 90%
Registration number	01-2119480383-37-0000
CAS number	107-15-3
EC number	203-468-6
Product code	5405288
Synonyms	Dimethylenediamine 90% 1,2 Diaminoethane 90%

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Uses advised against	No information
Applications of the substance	Intermediate in manufacture of sequestering agents, fungicides, textile resins and polyamide resins. Metal treatment

1.3 Details of the supplier of the safety data sheet

Supplier:
Alliance Chemicals Limited
Old Walls, Chapel Lane, Penselwood, BA9 8LY
United Kingdom
Telephone: +44 (0) 1747841222
Email: sj@alliancechemicals.com

1.4 Emergency telephone number

+44 1865 407333 NCEC 24 hr

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 2/57


2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (regulation (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI2019/720, and UK SI 2020/1567)	Flammable Liquids, Category 3, H226 Acute Toxicity, category 4, H302 Acute Toxicity, category 4, H332 Acute Toxicity, category 3, H311 Skin Corrosion, category 1B, H314 Respiratory Sensitisation, category 1B, H334 Skin Sensitisation, category 1B, H317 Chronic aquatic toxicity, category 3, H412
Classification (67/548/EEC, 1999/45/EC) Hazard category:	Flammable, R10 Corrosive, C, R34 Harmful, Xn, R42/43 Sensitising, Xn, R42/43
Risk advice to man and the environment	Flammable. Causes burns. Harmful in contact with skin and if swallowed. May cause sensitisation by inhalation and skin contact.

For a full text of H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Label (regulation (EC) 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567:	
Pictogram	
Signal word	Danger
Hazard statements	H226 Flammable liquid and vapour. H302 + H332 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe burns and eye damage. H317 May cause an allergic skin reaction. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H412 harmful to aquatic life with long lasting effects.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 3/57

<p>Precautionary statements</p>	<p>Prevention: P261 Avoid breathing dust/ fumes/ gas/ mist/ vapour/ spray. P280 Wear protective gloves/ protective clothing/ face protection/ eye protection. P285 In case of inadequate ventilation wear respiratory protection.</p> <p>Response: P303 + P361 + P353 IF ON SKIN (or hair): Remove/ take off immediately all contaminated clothing. Rinse skin with water/ shower P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.</p>
<p>Hazardous components which must be listed on the label:</p>	<p>Ethylenediamine 90% 107-15-3</p>

2.3 Other hazards

<p>No further data available</p>	
<p>PBT and vPvB assessment:</p>	<p>This substance/ mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.</p>

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 4/57

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances

Hazardous Substance					
Chemical Name	PBT vPvB -OEL	CAS-No. EC-No. REACH No.	Classification (REGULATION (EC) No 1272/2008)	Classification (67/548/EEC)	Conc %
Ethylenediamine		107-15-3 203-468-6 01- 2119480383 -37-0000	Flam.Liq.3; H226 Acute Tox. 4; H302 Acute Tox. 4; H3132 Acute Tox. 3; H311 Skin Corr. 1B; H314 Resp. Sens. 1; H334 Skin Sens. 1; H317	R10 C; 34 Xn; R20/R21/22 Sens: R42/43	90
Non Hazardous Substance:					
Water		7732-18-5 231-791-2			10

For the full text of H-Statements mentioned in this Section, see Section 16.

For the full text of R-Phrases mentioned in this Section, see Section 16.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59)
Status ·Ethylenediamine

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 5/57

4. FIRST AID MEASURES

4.1 Description of first aid measures

General Advice	Immediately seek medical attention. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	Remove to fresh air immediately. If not breathing give artificial respiration. Consult physician after significant exposure.
In case of skin contact	Remove contaminated clothes and shoes. Immediately flush with water for at least 15 minutes. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Take immediately to hospital.
In case of eye contact	Immediately rinse with water for at least 15 minutes holding the eyelids apart. Get medical attention. Remove contact lenses. Protect unharmed eye. Small amounts splashed into eye can cause irreversible tissue damage and blindness.
If swallowed	Wash mouth out with water and then drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately. DO NOT induce vomiting! May cause chemical burns in mouth and throat.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms:	The symptoms and effects are expected from the hazards as shown in Section 2. No specific product related symptoms are known.
Risks:	Harmful if swallowed or inhaled. Toxic in contact with skin. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes severe burns.

4.3 Indication of any immediate medical and special treatment needed

Symptomatic treatment. If in doubt get medical attention immediately

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 6/57

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents	Carbon dioxide (CO ₂), water spray, alcohol-resistant foam, dry chemical powder.
For safety reasons unsuitable extinguishing agents:	No information available.

5.2 Special hazards arising from the substance or mixture

Special hazards during firefighting/ Specific hazards arising from the chemical	Water spray may be ineffective unless used by experienced firefighters. Do not allow run-off from firefighting to enter drains of water courses.
Combustion products	Carbon oxides. Nitrogen oxides (NO _x).

5.3 Advice for firefighters

Special protective equipment for firefighters	Wear self-contained breathing apparatus and protective suit/ eye protection.
Additional information	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire cans should be stored separately in closed containments.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Wear protective clothing.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Remove all incompatible materials and sources of ignition.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Do not allow the product to penetrate the ground/soil.
Do not allow the product to reach any water course/ sewage systems.
If the product contaminates water courses/ sewage systems inform the respective authorities.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 7/57

6.3 Methods for cleaning up/ Methods for containment

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

6.4 Reference to other sections

For personal protection see section 8.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advise on safe handling:

For personal protection see Section 8.
Do not breath vapours or spray mist.
Avoid contact with skin and eyes.
Persons with a history of skin sensitisation problems, or asthma, allergies, chronic of recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating or drinking should be prohibited in the application area.
Provide sufficient air exchange and/ or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion:

Avoid formation of aerosol.
Keep away from sources of ignition – No Smoking.
Take measures to prevent build-up of electrostatic charge.
No sparking tools should be used.

7.2 Conditions for safe storage including any incompatibilities

Requirements for storage areas and containers:	No Smoking. Keep contained tightly closed in a dry and well ventilated place. Reacts with copper, aluminium, zinc and their alloys. Electrical installations/ working materials must comply with the technological safety standards.
Information about storage in one common storage facility:	Store away from feedstuffs or foodstuffs Avoid incompatible materials and conditions
Other data:	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

No special requirement

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 8/57

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Hazardous ingredients: 1,2-DIAMINOETHANE

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

DNEL (Derived No Effect Level)/ PNEC (Predicted No Effect Concentration) values according to Regulation (EC) No. 1907/2006

Type	Exposure	Value	Population	Effect
DNEL	Dermal	10 g/l	Workers	Acute local
DNEL	Dermal	3.6 mg/Kg bw/day	Workers	Long-term systemic
DNEL	Inhalation	25 mg/ m3	Workers	Long-term systemic
PNEC	Fresh water	0.016 mg/ l	-	-
PNEC	Marine water	0.002 mg/ l	-	-
PNEC	Fresh water sediment	7.68 mg/ Kg dry weight	-	-
PNEC	Marine sediment	0.768 mg/ Kg dry weight	-	-
PNEC	Soil	4.36 mg/ Kg dry weight	-	-
PNEC	Sewage treatment plant	0.5 mg/ l	-	-

8.2 Exposure controls

Engineering controls	Effective exhaust ventilation system. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal Protective equipment	
Respiratory protection:	In case of vapour formation use a respirator with an approved filter. Gas/ vapour filter, type K: ammonia and derivatives (EN141)
Hand protection:	Butyl-rubber gloves.
Eye protection:	Tight fitting safety goggles. Face-shield
Skin and body protection:	Protective suit
Hygiene measures:	Avoid contact with skin, eyes and clothing. When using do not eat, drink or smoke. Wash hands before break and end of work day. Wash contaminated clothing before re-use
Environmental exposure controls	
General advice	Prevent product from entering drains and waterways. If contamination occurs inform respective authorities.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 9/57

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Form: Colour: Odour: Odour threshold:	Liquid Colourless to light yellow Ammonical No data available
Safety data:	pH - Melting point - Boiling point - Flash point - Ignition temperature - Evaporation rate - Flammability - Lower explosion limit - Upper explosion limit - Vapour pressure - Relative vapour pressure - Relative density - Water solubility - Solubility in other solvents - Partition coefficient - Auto ignition temperature - Decomposition temperature - Viscosity - Explosive properties - Oxidizing properties -	12.8 @ 25% solution (20°C). 2°C 117°C 50°C (tag closed cup). Not determined. Not determined. Flammable. 4.2 vol. % 14.4 vol. % 13.8 hPa @ 20°C 2.1 (air = 1). 0.910 @ 20°C Miscible in all proportions (20°C). Miscible with ethanol, acetone and ether. Not determined. 406°C Not determined. 1.7 mPa.s @ 20°C Not explosive. Not classified as oxidizing.
This safety data only contains information relating to safety and does not replace any product information or product specification		

9.2 Other information

No further relevant information is available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical stability

Stable under recommended storage conditions (see Section 7). Stable under normal temperatures and pressures.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 10/57

10.3 Possibility of hazardous reactions

Heating can release hazardous gases.

10.4 Conditions to avoid

Conditions to avoid:	Heat, flames and sparks. Avoid contact with strong oxidizers. Fire or intense heat may cause violent rupture of package.
----------------------	--

10.5 Incompatible materials

Materials to avoid:	Reacts strongly with concentrated acids and chlorohydrocarbons. Attacks copper and copper alloys. Reacts strongly with oxidizers.
---------------------	---

10.6 Hazardous decomposition products

Hazardous decomposition products:	Hazardous decomposition will produce carbon monoxide and/or carbon dioxide. Nitrogen oxides (NOx).
Thermal decomposition:	No data available.

11. TOXICOLOGICAL INFORMATION

Product Information:

Hazard Summary	
Inhalation:	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation of aerosols may cause irritation to mucous membranes.
Skin:	Symptoms may be delayed. Toxic in contact with skin. May cause an allergic skin reaction. Causes severe skin burns.
Eyes:	Causes serious eye damage.
Ingestion:	Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Toxicological Assessment

Further information: Solvents may degrease the skin.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 11/57

11.1 Information on toxicological effects

Toxicological data for the components:

Test result ethylenediamine	
Acute oral toxicity:	LD50: > 300-2,000 mg/ Kg (rat).
Acute inhalation toxicity:	LD50: > 10-20 mg/l (rat). Exposure time 4h. Test atmosphere: vapour.
Acute dermal toxicity:	LD50: > 200-1000 mg/ Kg (rabbit).
Skin irritation:	Result: Causes burns.
Sensitisation:	Result: The product is a skin sensitiser, sub-category 1B. Result: The product is a respiratory sensitiser, sub-category 1B.
Germ cell mutagenicity	
Genotoxicity in vitro:	Result: No evidence of genotoxic effects in vitro.
Genotoxicity in vivo:	Result: No evidence of genotoxic effect in vivo.

12. ECOLOGICAL INFORMATION

Product Information:

Ecotoxicology Assessment	
Additional ecological information:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Ecotoxicology Assessment			
Product/ ingredient name	Result	Species	Exposure
Ethylenediamine	EC50: 3.2 g/l.	Micro-organism	2 hours
	NOEC: 0.5 g/l.	Micro-organism	2 hours
	Acute EC50: 645 mg/l Fresh water.	Algae	72 hours
	Acute EC50: 16.7 mg/l Fresh water.	Daphnia	48 hours
	Acute LC50: 640 mg/l fresh water.	Fish	96 hours
	Acute NOEC: 3.2 mg/l Fresh water.	Algae	72 hours
	Chronic NOEC: 0.16 mg/l Fresh water	Daphnia	21 days
	Chronic NOEC: 10 mg/l Fresh water	Fish	28 days

Conclusions/ Summary: PNEC Intermittent release = 0.167 mg/l (ethylenediamine)

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 12/57

12.2 Persistence and degradability

Ethylenediamine	
Biodegradability:	Result: Readily biodegradable. >60% BOD, 28 days, Closed Bottle Test (OECD 301D).

12.3 Bioaccumulative potential

Ethylenediamine	
Bioaccumulation:	Not expected considering the low log Pow value.

12.4 Mobility in soil

Ethylenediamine	
Mobility:	The product is miscible in water and readily biodegradable in both water and soil. Accumulation is not expected. Groundwater contamination is unlikely.

12.5 Results of PBT and vPvB assessment

Ethylenediamine	
PBT and VPvB assessment:	This substance is not considered to be PBT (Persistent, Bioaccumulative, Toxic) This substance is not considered to be vPvB (very Persistent nor very Bioaccumulative)

12.6 Other adverse effects

Ethylenediamine	
Biochemical Oxygen Demand (BOD):	No data available

Harmful to fauna.
Do not allow to enter watercourses or soils.
Large doses cause high/ low pH which may affect effluent and sewage treatment processes.
Discharge of large quantities may kill fish and other aquatic life due to increase/ decrease in ph.
Harmful to aquatic organisms.
Spillage in sewers or waterways must be avoided.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 13/57

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Product	This product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Hazardous waste
Contaminated packaging:	Contaminated packaging must not be treated as household waste. Dispose of in accordance with regional or national regulations. Do not burn, or use a cutting torch, on the empty packaging.

14. TRANSPORT INFORMATION

14.1 UN Number	
ADR:	1604
RID:	1604
IMDG-Code:	1604
IATA-DGR:	1604
14.2 Proper Shipping Name	
ADR:	ETHYLENEDIAMINE.
RID:	ETHYLENEDIAMINE.
IMDG-Code:	ETHYLENEDIAMINE.
IATA-DGR:	Ethylenediamine.
14.3 Transport Hazard Class	
ADR:	8 (3)
RID:	8 (3)
IMDG-Code:	8 (3)
IATA-DGR:	8 (3)
14.4 Packing Group	
ADR:	
Packaging Group:	11
Classification Code:	CF1
Hazard Identification No:	83
Labels:	8 (3)
Tunnel Restriction Code:	Full load, Tank-container, (D/E).
RID:	
Packaging Group:	11
Classification Code:	CF1
Hazard Identification No:	83
Labels:	8 (3)
IMDG-Code:	
Packaging Group:	11
Labels:	8 (3)
EmS Code:	F-E, S-C
IATA:	
Packing Instruction (Cargo Aircraft):	855
Packaging Group:	11
Labels:	8 (3)

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 14/57

14.5 Environmental Hazards	
ADR:	
Environmentally Hazardous:	No.
RID:	
Environmentally Hazardous:	No.
IMDG-Code:	
Marine Pollutant:	No.
IATA-DGR:	
Environmentally Hazardous:	No.

14.6 Special precautions for user:

Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Not applicable for product as supplied.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

Ethylenediamine	
UK REACH List of restrictions (Annex 17)	Conditions of restriction for the following entries should be considered: Number on list 40,3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	Ethylenediamine
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	Not applicable
GB export and import of hazardous chemicals- Prior Informed Consent (PIC) regulation	Not applicable
Control of Major Accident Hazards Regulations P5c 2015 (COMAH)	FLAMMABLE LIQUIDS
The components of this product are reported in the following inventories:	
CH INV:	YES. On the inventory, or in compliance with the inventory.
TSCA:	YES. All chemical substances in this product are either listed on the TSCA inventory or in compliance with a TSCA inventory exemption.
DSL:	YES. The Ethylenediamine component of this product is on the Canadian DSL list.

ETHYLENEDIAMINE 90% (EDA90%)

According to (EC) 1907/2006, as amended by UK REACH regulations SI 2019/758

Version: 13
Version Date: 25/07/2023

Page: 15/57

AICS:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
NZIoC:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
ENCS:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
ISHL:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
KECI:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
PICCS:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
IECSC:	YES. Ethylenediamine is on the inventory, or in compliance with the inventory.
Further Information:	
This product is to be considered a substance according to EU-legislation.	
Chemical Safety Assessment:	
Ethylenediamine:	A chemical safety assessment has been carried out for this substance.

16. OTHER INFORMATION

Full Text Of H-Statements Referred To Under Sections 2 And 3	
H226:	Flammable liquid and vapour.
H302:	Harmful if swallowed.
H311:	Toxic in contact with skin.
H314:	Causes severe burns and eye damage.
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H332:	Harmful if inhaled.
H334:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Full Text Of R-Phrases Referred To Under Sections 2 And 3	
R10:	Flammable.
R20/21/22:	Harmful by inhalation, in contact with skin, or if swallowed.
R34:	Causes burns.
R42/43:	May cause sensitisation by inhalation and skin contact.
Explanation For Possible Abbreviations Mentioned In Section 2	
PBT:	Persistent, bioaccumulative and toxic.
vPvB:	Very persistent and very bioaccumulative.
OEL:	Occupational exposure limit.

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 16/57

Annex:

Use as an intermediate
Industrial formulation
Industrial use as a processing aid
Industrial use, processing aid/ scavenging agent in refinery streams/ corrosion inhibitors
Heat and pressure transfer fluids in dispersive, professional use but closed systems
Monomer used in epoxy, PU, adhesives, coatings and other polymers, Industrial
Monomer used in epoxy, PU, adhesives, coatings and other polymers, Professional

1/. Short title of Exposure Scenario: Use as an intermediate

Main User Groups : SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Environmental Release Categories : ERC6a, ERC6c: Industrial use resulting in the manufacture of another substance (use of intermediates), Industrial use of monomers for manufacture of thermoplastics

Process Categories : PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch or other process (synthesis) where opportunity for exposure arises
PROC15: Use as a laboratory reagent

2.1/. Contributing scenario controlling environmental exposure for: ERC6a, ERC6c: Industrial use resulting in the manufacture of another substance (use of intermediates), Industrial use of monomers for manufacture of thermoplastics

Amount used

Maximum daily site tonnage : 500 kg/day
Fraction of EU tonnage used in region : 100%
Fraction of Regional tonnage used locally : 1%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 220
Emission or Release Factor: Air : 0.1%
Emission or Release Factor: Water : 0.7%
Emission or Release Factor: Soil : 0%
Additional risk management : 92%
Measures for water remarks : For example, incineration, ion exchange processes

Technical conditions and measures/
Organisational measures Exposure time : Continuous use. Release

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 17/57

2.2/. Contributing scenario controlling worker exposure for : PROC1: Use in closed process, no likelihood of exposure

Activity : General exposures, (closed systems)

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Outdoor/ Indoor : Outdoor

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.3/. Contributing scenario controlling worker exposure for: PROC2: Used in closed, continuous process with occasional controlled exposure

Activity : General exposures, Continuous process, (open systems)

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 18/57

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.4/. Contributing scenario controlling worker exposure for: PROC3: Use in closed batch process (synthesis or formulation)

Activity : Use in contained batch processes

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Technical conditions and measures

Local exhaust ventilation is required at any step if there is opportunity for significant exposure (Effectiveness (of a measure): 90%)

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.5/. Contributing scenario controlling worker exposure for: PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

Activity : Use in contained batch processes, Process sampling

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 19/57

Frequency and duration of use

Exposure duration : > 240 min
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Technical conditions and measures

Provide extraction ventilation at points where emissions occur (Effectiveness (of a measure): 90%)

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.6/. Contributing scenario controlling worker exposure for: PROC15: Use as laboratory reagent

Activity : Laboratory activities

Frequency and duration of use

Exposure duration : > 240 min
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Technical conditions and measures

Provide extraction ventilation at points where emissions occur (Effectiveness (of a measure): 90%)

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

3/. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC6a	EUSES		Fresh water		0.014 mg/L	0.86
			Fresh water sediment		6.613 mg/ kg dry weight	0.86
			Marine water		0.001 mg/L	0.688
			Marine sediment		0.66 mg/ kg dry weight	0.859
			Sewage treatment plant		0.134 mg/ L	0.269
			Soil		1.176 mg/ kg dry weight	0.27

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC1	ECETOC TRA v3.0		Long term inhalation	0.025 mg/m ³	<0.01
			Long term dermal	0.002 mg/kg bw/day	<0.01
PROC2	ECETOC TRA v3.0		Long term inhalation	1.252 mg/m ³	0.05
			Long term dermal	0.068 mg/kg bw/day	0.019
PROC3	ECETOC TRA		Long term inhalation	2.504 mg/m ³	.1
			Long term dermal	0.034 mg/kg bw/day	<0.01
PROC4	ECETOC TRA v3.0		Long term inhalation	5.008 mg/m ³	0.2
			Long term dermal	0.343 mg/kg bw/day	0.095
PROC15	ECETOC TRA v3.0		Long term inhalation	1.502 mg/m ³	0.06
			Long term dermal	0.01 mg/kg bw/day	<0.01

ERC6a: Industrial use resulting in manufacture of another substance (use of Intermediates)

ERC6c: Industrial use of monomers for the manufacture of thermoplastics

PROC1: Use in closed process, no likelihood of exposure

PROC15: Use as a laboratory reagent

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure Arises

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 21/57

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 22/57

1/. Short title of Exposure Scenario: Industrial formulation

Main User Groups : SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Environmental Release

Categories : ERC2: Formulation of preparations

Process Categories : PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch or other process (synthesis) where opportunity for exposure arises
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC9: transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC15: Use as a laboratory reagent

2.1/. Contributing scenario controlling environmental exposure for: ERC2: Formulation or preparations

Amount used

Maximum daily site tonnage : 6300 kg/day
Fraction of EU tonnage used in region : 100%
Fraction of Regional tonnage used locally : 10%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 220
Emission or Release Factor: Air : 0.03%
Emission or Release Factor: Water : 0.05%
Emission or Release Factor: Soil : 0.01%
Remarks : spERC: ESVOC SpERC 2.2.v1
Additional risk management : 90%
Measures for water remarks : For example, incineration, ion exchange processes

Technical conditions and measures/

Organisational measures

Exposure time : Continuous use/release

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 23/57

2.2/. Contributing scenario controlling worker exposure for : PROC3: Use in closed batch process (synthesis or formulation)

Activity : Use in contained batch processes

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.3/. Contributing scenario controlling worker exposure for: PROC4: Used in batch and other process (synthesis) where opportunity for exposure arises

Activity : Use in contained batch processes, Process sampling

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 24/57

Other operational conditions affecting workers exposure
Outdoor/ Indoor : **Indoor**

Technical conditions and measures
Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure
Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation
Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.4/. Contributing scenario controlling worker exposure for: PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

Activity : Use in contained batch processes

Product characteristics
Concentration of the substance in Mixture/ Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)
Physical Form (at time of use) : liquid

Frequency and duration of use
Exposure duration : > 240 min
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management
Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure
Outdoor/ Indoor : **Indoor**
Ventilation rate per hour : 1
Remarks : Any Room size

Exposure routes
Inhalation exposure, Dermal exposure

Technical conditions and measures
Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 50%)
Use in contained systems (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure
Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation
Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 25/57

2.5/. Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Activity : Drum/batch transfers/ Bulk transfers

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : < 15 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands (960 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Mass transfer rate : 1-10 L/min

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.6/. Contributing scenario controlling worker exposure for: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at facilities

Activity : Drum/batch transfers/ Bulk transfers

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : 1-4 h

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 26/57

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 95%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.7/. Contributing scenario controlling worker exposure for: PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Activity : Drum and small package filling, Small package filling

Product characteristics

**Concentration of the substance in Mixture/
Article** : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : 1-4 h
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.8/. Contributing scenario controlling worker exposure for: PROC15: Use as a laboratory reagent

Activity : Laboratory activities

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 100% (unless stated differently)

Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : <240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

3/. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC2	EUSES		Fresh water		0.015 mg/L	0.965
			Fresh water sediment		7.414 mg/ kg dry weight	0.965
			Marine water		0.002 mg/L	0.77
			Marine sediment		0.74 mg/ kg dry weight	0.965
			Sewage treatment plant		0.151 mg/ L	0.302
			Soil		1.322 mg/ kg dry weight	0.303

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC3	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.034 mg/kg bw/day	<0.01
PROC4	ECETOC TRA v3.0		Long term inhalation	5.008 mg/m ³	0.2
			Long term dermal	0.343 mg/kg bw/day	0.095
PROC5	ART		Long term inhalation	2.6 mg/m ³	.104
	ECETOC TRA v3.0		Long term dermal	0.686 mg/kg bw/day	0.19
PROC8a	ART		Long term inhalation	3.1 mg/m ³	0.124
	ECETOC TRA v3.0		Long term dermal	0.069 mg/kg bw/day	0.019
PROC8b	ART		Long term inhalation	1.878 mg/m ³	0.075
	ECETOC TRA v3.0		Long term dermal	0.411 mg/kg bw/day	0.114
PROC9	ECETOC TRA v3.0		Long term inhalation	1.502 mg/m ³	0.06
			Long term dermal	0.041 mg/kg bw/day	0.011
PROC15	ECETOC TRA v3.0		Long term inhalation	1.502 mg/m ³	0.06
			Long term dermal	0.01 mg/kg bw/day	<0.01

ERC2: Formulation of preparation

PROC15: Use as a laboratory reagent

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure Arises

PROC5: Mixing or blending in batch processes for formulation of preparations and Articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to Vessels/ large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to Vessels/ large containers at facilities

PROC9: Transfer of substance or preparation into small containers (dedicated Filling line, including weighing)

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 29/57

1/. Short title of Exposure Scenario: Industrial use as a processing aid

Main User Groups : SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Environmental Release Categories : ERC4, ERC7: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use of substances in closed systems

Process Categories : PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)

2.1/. Contributing scenario controlling environmental exposure for: ERC4, ERC7: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use of substances in closed systems

Amount used

Maximum daily site tonnage : 500 kg/day
Fraction of EU tonnage used in region : 100%
Fraction of Regional tonnage used locally : 0.046%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 20
Emission or Release Factor: Air : 1%
Emission or Release Factor: Water : 0.01%
Emission or Release Factor: Soil : 0.1%
Remarks : ESVOC SpERC 7.13.v1

Technical conditions and measures/

Organisational measures

Exposure time : Continuous use/release
Compartment : Fresh water, Fresh water sediment, Marine water, Marine sediment, Soil, Grassland, Sewage treatment plant

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

2.2/. Contributing scenario controlling worker exposure for : PROC1: Use in closed process, no likelihood of exposure

Activity : General exposures, (closed systems)

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 30/57

Product characteristics

**Concentration of the substance in Mixture/
Article** : Covers the percentage of the substance in the product up to 25%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.) Effectiveness (of a measure): 95%

2.3/. Contributing scenario controlling worker exposure for: PROC2: Used in closed, continuous process with occasional controlled exposure

Activity : General exposures, Continuous process, (open systems)

Product characteristics

**Concentration of the substance in Mixture/
Article** : Covers the percentage of the substance in the product up to 25%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ Indoor : Outdoor

Exposure Routes

Inhalation exposure, dermal exposure

Component: Ethylenediamine (EDA)
 Version: 13
 Version Date: 25/07/2023

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
 Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%)

3/. Exposure estimation and reference to its source
--

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC4	EUSES		Fresh water		0.0007 mg/L	0.041
			Fresh water sediment		0.318 mg/ kg dry weight	0.041
			Marine water		0.0001 mg/L	0.033
			Marine sediment		0.031 mg/ kg dry weight	0.041
			Sewage treatment plant		0.002 mg/ L	<0.01
			Soil		0.022 mg/ kg dry weight	<0.01

Component:
Version:
Version Date:

Ethylenediamine (EDA)
13
25/07/2023

Page: 32/57

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC1	ECETOC TRA v3.0		Long term inhalation	0.015 mg/m ³	<0.01
			Long term dermal	0.002 mg/kg bw/day	<0.01
PROC2	ECETOC TRA v3.0		Long term inhalation	7.512 mg/m ³	0.3
			Long term dermal	0.041 mg/kg bw/day	0.011
PROC3	ECETOC TRA v3.0		Long term inhalation	1.502 mg/m ³	0.06
	ECETOC TRA v3.0		Long term dermal	0.021 mg/kg bw/day	<0.01

ERC4: Industrial use of processing aids in processes and products, not becoming part Of articles

ERC7: Industrial use of substances in closed systems

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario
--

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 33/57

1/. Short title of Exposure Scenario: Industrial use, Processing aid/ Scavenging agent in refinery streams/ Corrosion inhibitors

Main User Groups : SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Environmental Release Categories : ERC4, ERC7: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use of substances in closed systems

Process Categories : PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)

2.1/. Contributing scenario controlling environmental exposure for: ERC4. ERC7: Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use of substances in closed systems

Amount used

Maximum daily site tonnage : 6000 kg/day
Fraction of EU tonnage used in region : 100%
Fraction of Regional tonnage used locally : 10%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Air : 0.25%
Emission or Release Factor: Water : 0.001%
Emission or Release Factor: Soil : 0.0%
Remarks : spERC: ESVOC SpERC 7.12a.v1

Technical conditions and measures/

Organisational measures

Exposure time : Continuous use/release
Compartment : Fresh water, Fresh water sediment, Marine water, Marine sediment, Soil, Grassland, Sewage treatment plant

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

2.2/. Contributing scenario controlling worker exposure for : PROC1: Use in closed process, no likelihood of exposure

Activity : General exposures, (closed systems)

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 25%

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Remarks : Inhalation, Dermal

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Outdoor/ indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.) Effectiveness (of a measure): 90%

2.3/. Contributing scenario controlling worker exposure for: PROC2: Used in closed, continuous process with occasional controlled exposure

Activity : General exposures, Continuous process, (open systems)

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 25%

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 35/57

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ Indoor : Outdoor

Exposure Routes

Inhalation exposure, dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.4/. Contributing scenario controlling worker exposure for: PROC3: Use in closed batch process (synthesis or formulation)

Activity : Use in contained batch processes

Product characteristics

Concentration of the substance in Mixture/ Article : Covers the percentage of the substance in the product up to 25%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ Indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 50%)
Use in contained systems (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
 Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%)

3/. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC4	EUSES		Fresh water		0.0001 mg/L	0.042
			Fresh water sediment		0.341 mg/ kg dry weight	0.044
			Marine water		0.0001 mg/L	0.035
			Marine sediment		0.034 mg/ kg dry weight	0.044
			Sewage treatment plant		0.003 mg/ L	<0.01
			Soil		0.027 mg/ kg dry weight	<0.01

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC1	ECETOC TRA v3.0		Long term inhalation	0.015 mg/m ³	<0.01
			Long term dermal	0.002 mg/kg bw/day	<0.01
PROC2	ECETOC TRA v3.0		Long term inhalation	7.512 mg/m ³	0.3
			Long term dermal	0.041 mg/kg bw/day	0.011
PROC3	ECETOC TRA v3.0		Long term inhalation	1.502 mg/m ³	0.06
	ECETOC TRA v3.0		Long term dermal	0.021 mg/kg bw/day	<0.01

ERC4: Industrial use of processing aids in processes and products, not becoming part Of articles

ERC7: Industrial use of substances in closed systems

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 37/57

1/. Short title of Exposure Scenario: Heat and pressure transfer fluids in dispersive, professional use but closed systems

Main User Groups : SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Environmental Release Categories : ERC9a, ERC9b: Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems
Process Categories : PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems

2.1/. Contributing scenario controlling environmental exposure for: ERC9a, ERCb: Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems

Amount used

Maximum daily site tonnage : 12 kg/day
Fraction of EU tonnage used in region : 10%
Fraction of Regional tonnage used locally : 0.2%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Air : 5%
Emission or Release Factor: Water : 5%
Emission or Release Factor: Soil : 5%

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

2.2/. Contributing scenario controlling worker exposure for : PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems

Activity : (closed systems)

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Component: Ethylenediamine (EDA)
 Version: 13
 Version Date: 25/07/2023

Page: 38/57

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
 Outdoor/ indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable protective clothing

3/. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC9a	EUSES		Fresh water		0.003 mg/L	0.208
			Fresh water sediment		1.595 mg/ kg dry weight	0.208
			Marine water		0.0003 mg/L	0.166
			Marine sediment		0.159 mg/ kg dry weight	0.207
			Sewage treatment plant		0.029 mg/ L	0.058
			Soil		0.256 mg/ kg dry weight	0.059

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC20	ECETOC TRA v3.0		Long term inhalation	7.011 mg/m ³	0.28
			Long term dermal	0.342 mg/kg bw/day	0.095

ERC9a: Wide dispersive indoor use of substances in closed systems
 ERC9b: Wide dispersive outdoor use of substances in closed systems
 PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed Systems

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 39/57

1/. Short title of Exposure Scenario: Monomer use in epoxy, PU, adhesives, coatings and other polymers, Industrial

Main User Groups : SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Environmental Release Categories : ERC6a, ERC6b, ERC6c, ERC6d: Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

Process Categories : PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
PROC7: Industrial spraying
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC10: Roller application or brushing
PROC13: Treatment of articles by dipping or pouring
PROC14: Production of preparations or articles by tableting, compression, extrusion, palletisation
PROC19: Hand-mixing with intimate contact and only PPE available
PROC24: High (mechanical) energy work-up of substances bound in materials and/ or articles

2.1/. Contributing scenario controlling environmental exposure for: ERC5: Industrial use resulting in inclusion into or onto a matrix

Amount used

Maximum daily site tonnage : 800 kg/day
Fraction of EU tonnage used in region : 100%
Fraction of Regional tonnage used locally : 10%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10

Other given operational conditions affecting environmental exposure

Number of emission days per year : 220
Emission or Release Factor: Air : 1.7%
Emission or Release Factor: Water : 0%
Emission or Release Factor: Soil : 0%
Remarks : SpERC: FEICA 5.1b.v1

Technical conditions and measures/

Organisational measures

Exposure time : Continuous use/release
Compartment : Fresh water, Fresh water sediment, Marine water, Marine sediment, Soil, Grassland, Sewage treatment plant

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 40/57

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 100%

2.2/. Contributing scenario controlling worker exposure for : PROC5: Mixing or blending in batch process for formulation of preparations and articles (multistage and/or significant contact)

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 4 h
Frequency of use : <= 240 days/ year
Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.3/. Contributing scenario controlling worker exposure for: PROC7: Industrial spraying

Activity : Spraying, Spraying (automatic/ robotic)

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 1%
Physical Form (at time of use) : liquid

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 41/57

Frequency and duration of use

Exposure duration : > 240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands plus forearms (1500 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure Routes

Inhalation exposure, dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%)

2.4/. Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/ discharging) from/to vessel/large containers at non-dedicated facilities

Activity : Drums/batch transfers, Bulk transfers
Product characteristics
Concentration of the substance in Mixture/ Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands (960 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 42/57

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.5/. Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing

Activity : Roller, spreader, flow application

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : >240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands (960 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%

2.6/. Contributing scenario controlling worker exposure for: PROC13: Treatment of articles by dipping and pouring

Activity : dipping, immersion and pouring

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 43/57

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

**Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.) Effectiveness (of a measure): 95%)**

2.7/. Contributing scenario controlling worker exposure for: PROC14: Production of preparations of articles by tableting, compression, extrusion, pelletisation
--

Activity : Production of preparations of articles by tableting, compression, extrusion, palletisation

Product characteristics

Concentration of the substance in Mixture/ Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 4 h
Remarks : Covers daily exposures up to 8 hours (unless stated differently)
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 44/57

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

2.8/. Contributing scenario controlling worker exposure for: PROC19: Hand mixing with intimate contact and only PPE available

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 5%

Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of the activity : 15 min – 1 h

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands and main part of arm (1980 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.

Wear suitable gloves (tested to EN374) in combination with specific activity training. (Effectiveness (of a measure): 95%)

Wear a respirator conforming to EN140 with type A filter or better. (Effectiveness (of a measure): 90%)

2.9/. Contributing scenario controlling worker exposure for: PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 1%

Physical Form (at time of use) : Solid mixture, Dustiness: Medium

Frequency and duration of use

Duration of the activity : >4 h

Frequency of use : <= 240 days/ year

Remarks : Covers daily exposure up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 45/57

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ Indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

3/. Exposure estimation and reference to its source
--

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC5	EUSES		Fresh water		0.0004 mg/L	0.027
			Fresh water sediment		0.204 mg/ kg dry weight	0.027
			Marine water		0.0001 mg/L	0.021
			Marine sediment		0.02 mg/ kg dry weight	0.026
			Sewage treatment plant		0 mg/ L	<0.01
			Soil		0.002 mg/ kg dry weight	<0.01

Component:
Version:
Version Date:

Ethylenediamine (EDA)
13
25/07/2023

Page: 46/57

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC5	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.137 mg/kg bw/day	0.038
PROC7	ECETOC TRA v3.0		Long term inhalation	3.13 mg/m ³	0.125
			Long term dermal	0.214 mg/kg bw/day	0.06
PROC8a	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.137 mg/kg bw/day	0.038
PROC10	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.274 mg/kg bw/day	0.076
PROC10	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.274 mg/kg bw/day	0.076
PROC13	ECETOC TRA v3.0		Long term inhalation	2.504 mg/m ³	0.1
			Long term dermal	0.137 mg/kg bw/day	0.038
PROC19	ECETOC TRA v3.0		Long term inhalation	0.501 mg/m ³	0.02
			Long term dermal	0.283 mg/kg bw/day	0.079
PROC24	ECETOC TRA v3.0	Indoor	Long term inhalation	1 mg/m ³	0.04
		Outdoor	Long term inhalation	0.75 mg/m ³	0.03
			Long term dermal	0.288 mg/kg bw/day	0.08

ERC5: Industrial use resulting in inclusion into or onto a matrix

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping or pouring

PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation

PROC19: Hand mixing with intimate contact and only PPE available

PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 47/57

4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstream_users_en.htm

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 48/57

1/. Short title of Exposure Scenario: Monomer use in epoxy, PU, adhesives, coatings and other polymers, Professional

Main User Groups : SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Environmental Release Categories : ERC8c, ERC8f: wide dispersive indoor use resulting in inclusion into or onto a matrix, Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Process Categories : PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC10: Roller application or brushing
PROC11: Non industrial spraying
PROC13: Treatment of articles by dipping or pouring
PROC14: Production of preparations or articles by tableting, compression, extrusion, palletisation
PROC19: Hand-mixing with intimate contact and only PPE available

2.1/. Contributing scenario controlling environmental exposure for: ERC8c, ERC8f: Wide dispersive indoor use resulting in inclusion into or onto a matrix, Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amount used

Maximum daily site tonnage : 2 kg/day
Fraction of EU tonnage used in region : 10%
Fraction of Regional tonnage used locally : 0.2%

Environmental factors not influenced by risk management

Flow rate : 18000 m³/ day
Dilution Factor (River) : 10

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Air : 0%
Emission or Release Factor: Water : 1.5%
Emission or Release Factor: Soil : 0%
Remarks : SpERC: FEICA 8c.1a.v1

Technical conditions and measures/

Organisational measures

Exposure time : Continuous use/release
Compartment : Fresh water, Fresh water sediment. Marine water, Marine sediment, Soil, Grassland, Sewage treatment plant

Conditions and measures related to municipal sewage water treatment plant

Type of Sewage Treatment Plant : Municipal sewage treatment plant
Flow rate of sewage treatment plant effluent: 2,000 m³/ day
Percentage removed from waste water : 90.4%

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 49/57

2.2/. Contributing scenario controlling worker exposure for : PROC5: Mixing or blending in batch process for formulation of preparations and articles (multistage and/or significant contact)

Activity : Indoor

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 4 h
Frequency of use : <= 240 days/ year
Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Palm of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Ventilation rate per hour : 3
Remarks : Use in large workrooms only

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

2.3/. Contributing scenario controlling worker exposure for: PROC5: Mixing or blending in batch process for formulation of preparations and articles (multistage and/or significant contact)

Activity : Outdoor

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : > 4 h
Remarks : Covers daily exposures up to 8 hours (unless Stated differently)
Frequency of use : <= 240 days/ year

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 50/57

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Outdoor

Exposure Routes

Inhalation exposure, dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

2.4/. Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/ discharging) from/to vessel/large containers at non-dedicated facilities

Activity : Indoor

Product characteristics

Concentration of the substance in Mixture/

Article : Covers the percentage of the substance in the product up to 5%

Physical Form (at time of use) : liquid

Frequency and duration of use

Exposure duration : > 4 h

Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Both hands (960 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Ventilation rate per hour : 3

Remarks : Use in large workrooms only

Mass transfer rate : 10-100 L/min

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 51/57

2.5/. Contributing scenario controlling worker exposure for: PROC8a: Transfer of substance or preparation (charging/ discharging) from/to vessel/large containers at non-dedicated facilities

Activity : Outdoor

Product characteristics
Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use
Exposure duration : > 4 h
Remarks : Covers daily exposures up to 8 hours (unless Stated differently)
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management
Dermal exposure : Both hands (960 cm²)

Other operational conditions affecting workers exposure
Outdoor/ Indoor : outdoor

Exposure routes
Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure
Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation
Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

2.6/. Contributing scenario controlling worker exposure for: PROC10: Roller application or brushing

Activity : Roller, spreader, flow application

Product characteristics
Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 1%
Physical Form (at time of use) : liquid

Frequency and duration of use
Duration of activity : >240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year
Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management
Dermal exposure : Both hands (960 cm²)

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 52/57

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Ventilation rate per hour : 3
Remarks : Use in large workrooms only
Outdoor/ Indoor : Outdoor
Spreading of liquids on surfaces or work pieces : > 3 m²/hour

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 80%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374) in combination with specific activity training. (Effectiveness (of a measure): 80%)
In case no LEV is present, a suitable respiratory protection with adequate effectiveness is required. Wear a respirator conforming to EN140 with Type A filter or better. (Effectiveness (of a measure): 90%)

2.7/. Contributing scenario controlling worker exposure for: PROC11: Non industrial spraying

Activity : Spraying, Manual

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 1%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : >240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year
Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Both hands plus forearms (1500 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
Outdoor/ Indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 53/57

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374) in combination with specific activity training. (Effectiveness (of a measure): 80%)
Wear a respirator conforming to EN140 with Type A filter or better. (Effectiveness (of a measure): 90%)

2.8/. Contributing scenario controlling worker exposure for: PROC13: Treatment of articles by dipping and pouring

Activity : Dipping, immersion and pouring

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of activity : >240 min
Remarks : Inhalation, Dermal
Frequency of use : <= 240 days/ year
Remarks : Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur. (Effectiveness (of a measure): 80%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). (Effectiveness (of a measure): 80%)

2.9/. Contributing scenario controlling worker exposure for: PROC14: Production of preparations of articles by tableting, compression, extrusion, pelletisation

Product characteristics

Concentration of the substance in Mixture/
Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 54/57

Frequency and duration of use

Exposure duration : > 4 h
Remarks : Covers daily exposures up to 8 hours (unless stated differently)
Frequency of use : <= 240 days/ year

Human factors not influenced by risk management

Dermal exposure : Palms of both hands (480 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Technical conditions and measures

Provide extraction ventilation at points where emissions occur (Effectiveness (of a measure): 90%)

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
Wear suitable gloves (tested to EN374). Effectiveness (of a measure): 80%

2.10/. Contributing scenario controlling worker exposure for: PROC19: Hand mixing with intimate contact and only PPE available

Product characteristics

Concentration of the substance in Mixture/ Article : Covers the percentage of the substance in the product up to 5%
Physical Form (at time of use) : liquid

Frequency and duration of use

Duration of the activity : < 1 h
Frequency of use : <= 240 days/ year
Exposure duration : < 1 h

Human factors not influenced by risk management

Dermal exposure : Both hands and main part of arms (1980 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

Component: Ethylenediamine (EDA)
 Version: 13
 Version Date: 25/07/2023

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin.
 Wear suitable gloves (tested to EN374). (Effectiveness (of a measure): 80%)
 Wear a respirator conforming to EN140 with Type A filter or better. (Effectiveness (of a measure): 90%)

2.11/. Contributing scenario controlling worker exposure for: PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles

Product characteristics

Concentration of the substance in Mixture/
 Article : Covers the percentage of the substance in the product up to 1%
 Physical Form (at time of use) : Solid, medium dustiness

Frequency and duration of use

Duration of the activity : >4 h
 Frequency of use : <= 240 days/ year
 Remarks : Covers daily exposure up to 8 hours (unless stated differently)

Human factors not influenced by risk management

Dermal exposure : Palm of one hand (240 cm²)

Other operational conditions affecting workers exposure

Outdoor/ Indoor : Indoor
 Outdoor/ Indoor : Outdoor

Exposure routes

Inhalation exposure, Dermal exposure

Organisational measures to prevent/ limit releases, dispersion and exposure

Assume a good basic standard of occupational hygiene is implemented

3/. Exposure estimation and reference to its source

Environment

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Compartment	Value	Level of Exposure	RCR
ERC8c	EUSES		Fresh water		0.0006 mg/L	0.035
			Fresh water sediment		0.272 mg/ kg dry weight	0.035
			Marine water		0.0001 mg/L	0.028
			Marine sediment		0.026 mg/ kg dry weight	0.034
			Sewage treatment plant		0.002 mg/ L	<0.01
			Soil		0.014 mg/ kg dry weight	<0.01

Component:
Version:
Version Date:

Ethylenediamine (EDA)
13
25/07/2023

Page: 56/57

Workers

Contributing Scenario	Exposure Assessment Method	Specific Conditions	Value	Level of Exposure	RCR
PROC5	ART	Indoor	Long term inhalation	1.9 mg/m ³	0.076
	ECETOC TRA v3.0		Long term dermal	0.548 mg/kg bw/day	0.152
PROC5	ART	Outdoor	Long term inhalation	0.69 mg/m ³	0.028
	ECETOC TRA v3.0		Long term dermal	0.548 mg/kg bw/day	0.152
PROC8a	ART	Indoor	Long term inhalation	5.8 mg/m ³	0.232
	ECETOC TRA v3.0		Long term dermal	0.548 mg/kg bw/day	0.152
PROC8a	ART	Outdoor	Long term inhalation	2.1 mg/m ³	0.084
	ECETOC TRA v3.0		Long term dermal	0.548 mg/kg bw/day	0.152
PROC10	ART	Indoor	Long term inhalation	0.58 mg/m ³	0.023
	ART	Outdoor	Long term inhalation	1.764 mg/m ³	0.071
	ECETOC TRA v3.0		Long term dermal	0.549 mg/kg bw/day	0.152
PROC11	ART	Indoor	Long term inhalation	3.8 mg/m ³	0.152
	ART	Outdoor	Long term inhalation	1.4 mg/m ³	0.056
	ECETOC TRA v3.0		Long term dermal	2.143 mg/kg bw/day	0.595
PROC13	ECETOC TRA v3.0		Long term inhalation	10.02 mg/m ³	0.401
			Long term dermal	0.548 mg/kg bw/day	0.152
PROC14	ECETOC TRA v3.0		Long term inhalation	10.02 mg/m ³	0.401
			Long term dermal	0.137 mg/kg bw/day	0.038
PROC19	ECETOC TRA v3.0		Long term inhalation	1.002 mg/m ³	0.04
			Long term dermal	0.1.131 mg/kg bw/day	0.314
PROC24	ECETOC TRA v3.0	Indoor	Long term inhalation	2 mg/m ³	0.08
		Outdoor	Long term inhalation	1.5 mg/m ³	0.06
			Long term dermal	0.288 mg/kg bw/day	0.08

Component: Ethylenediamine (EDA)
Version: 13
Version Date: 25/07/2023

Page: 57/57

ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix
PROC10: Roller application or brushing
PROC11: Non industrial spraying
PROC13: Treatment of articles by dipping or pouring
PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
PROC19: Hand mixing with intimate contact and only PPE available
PROC24: High (mechanical) energy work-up of substances bound in materials and/or articles
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

<p>4/. Guidance to Downstream Users to evaluate whether he works inside the boundaries set by the Exposure Scenario</p>

For further information, please also consult the Internet site: Downstream Users
http://guidance.echa.europa.eu/downstrem_users_en.htm